

Efficiency

- Advanced MPPT technology with up to 99.9% efficiency
- Up to 22A PV input current for high power PV module

Safety

- 360 degrees of security from hardware to software
- IEC safety approvals

All in one

• Up to 100A charging current

Reliable

- Outputs high quality pure sine wave AC power
- Up to 6 units in parallel connection

User-Friendly

- Industrial design with a modern aesthetic look
- Easy to install and simple to use

Intelligent

- Exclusive Li-ion battery BMS dual activation
- Time-slot function to save cost with peak-valley

Application scenario













MODEL SYP 5K-U **INVERTER OUTPUT** Rated Output Power 5,000W Max.Peak Power 10,000VA Rated Output Voltage 120Vac (L/N/PE single-phase) \checkmark 4HP Load Capacity of Motors Rated AC Frequency 50/60Hz Waveform Pure sine wave Switch Time 10ms (typical) Parallel Capacity 1-6 units (single/split/three phase) **BATTERY** Li-ion / Lead-acid / User-define Battery Type Rated Battery Voltage 48Vdc Voltage Range 40~60Vdc 100A Max.MPPT Charging Current Max.Mains/Generator Charging Current 40A Max. Hybrid Charging Current 100A PV INPUT Num. of MPPT 1 Max.PV array power 5,500W 22A Max.input current Max. Voltage of Open Circuit 500Vdc 120~450Vdc MPPT Voltage Range MAINS / GENERATOR INPUT 90~140Vac Input Voltage Range 50/60Hz Frequency Range **Bypass Overload Current** 63A **EFFICIENCY** 99.9% MPPT Tracking Efficiency 92% Max. Battery Inverter Efficiency **GENERAL** 446.9*350*133mm (1.47*1.15*0.44ft) Dimensions Weight 14kg (30.86lb) Protection Degree IP20, indoor only -10~55°C Operating Temperature Range ≤60dB Noise Forced air cooling with adjustable air speed Cooling Method 18 months Warranty COMMUNICATION RS485 / USB / Dry contact Embedded Interfaces External Modules (Optional) Wi-Fi / GPRS CERTIFICATION CE(IEC 62109-1/2) Safety **EMC** EN61000 RoHS Yes